

nShield Solo

- · Maximize performance and availability with high cryptographic transaction rates and flexible scaling
- Supports a wide variety of applications including certificate authorities, code signing and more
- nShield CodeSafe protects your applications within nShield's secure execution environment
- on Shield Remote Administration helps you cut costs and reduce travel



nShield Solo HSMs

Certified PCI-Express cards that deliver cryptographic key services to stand-alone servers



nShield Solo HSMs

Feature Overview



The nShield Solo series includes nShield Solo+ and the new, high-performance nShield Solo XC.

HIGHLY FLEXIBLE ARCHITECTURE

nCipher unique Security World architecture lets you combine nShield HSM models to build a mixed estate that delivers flexible scalability and seamless failover and load balancing.

PROCESS MORE DATA FASTER

nShield Solo HSMs support high transaction rates, making them ideal for enterprise, retail, IoT and other environments where throughput is critical.

PROTECT YOUR PROPRIETARY APPLICATIONS AND DATA

The CodeSafe option provides a secure environment for running sensitive applications within nShield boundaries.

Supported cryptographic algorithms

- Asymmetric algorithms: RSA, Diffie-Hellman, ECMQV, DSA, El-Gamal, KCDSA, ECDSA, ECDH, Edwards (X25519, Ed25519ph)
- Symmetric algorithms: AES, Arcfour, ARIA, Camellia, CAST, DES, MD5 HMAC, RIPEMD160 HMAC, SEED, SHA-1 HMAC, SHA-224 HMAC, SHA-256 HMAC, SHA-384 HMAC, SHA-512 HMAC, Tiger HMAC, Triple DES
- Hash/message digest: MD5, SHA-1, SHA-2 (224, 256, 384, 512 bit), HAS-160, RIPEMD160
- Full Suite B implementation with fully licensed ECC, including Brainpool and custom curves

Supported operating systems

- o Microsoft Windows 7 x64, 10 x64; Windows Server 2008 R2 x64, 2012 R2 x64, 2016 x64
- Red Hat Enterprise Linux AS/ES 6 x64, 7 x64; SUSE Enterprise Linux 11 x64 SP2, 12 x64
- o Oracle Solaris 11 (SPARC), Oracle Solaris 11 x64
- Solo+: Red Hat Enterprise Linux AS/ES 6 x86, IBM AIX 7.1 (POWER6), HP-UX 11i v3
- o Oracle Enterprise Linux 6.8 x64 and 7.1 x64
- Solo XC virtual environment support: Microsoft Windows Hyper-V Server 2016, VMware ESXi 6.5, Citrix XenServer 6.5



Application programming interfaces (APIs)

• PKCS#11, OpenSSL, Java (JCE), Microsoft CAPI and CNG, nCore, nShield Web Services Crypto API

Host connectivity

• PCI Express Version 2.0; Solo+ connector: 1 lane, Solo XC connector: 4 lane

Security compliance

- FIPS 140-2 Level 2 and Level 3 certified
- Solo+: Common Criteria EAL4+ (AVA_VAN.5) certified
- Solo+ recognized as a Qualified Signature Creation Device
- Solo XC: BSI AIS 20/31 compliant

Safety and Environmental Standards Compliance

- UL, UL/CA, CE, FCC, Canada ICES, KC, FCC, VCCI, C-TICK, RCM
- o RoHS2, WEEE, REACH

Management and monitoring

- o nShield Remote Administration and nShield Monitor
- Secure audit logging
- Syslog diagnostics support and Windows performance monitoring
- SNMP monitoring agent

Dimensions	We	eight	Power	
	Solo+	Solo XC	Solo+	Solo XC
56.2 × 167.1 × 15.4mm	230g	280g	1014	24W
2.2 × 6.6 × 0.6in	0.5lb	0.62lb	10W	

AVAILABLE MODELS AND PERFORMANCE

nShield Solo Models	500+	XC Base	6000+	XC Mid	XC High		
RSA Signing Performance (tps) for NIST Recommended Key Lengths							
2048 bit		430	3,000	3,500	8,600		
4096 bit		100	500		2,025		
ECC Prime Curve Signing Performance (tps) for NIST Recommended Key Lengths							
	540		2,400	5,500	14,400		

LEARN MORE

To find out more how nCipher Security can deliver trust, integrity and control to your business critical information and applications, visit ncipher.com















